

MASONRY SAND



Tileco, Inc. ■ 91-209 Hanua Street ■ Kapolei, Hawaii 96707 ■ Ph: 808.682.5737 ■ Fax: 808.682.1013

DESCRIPTION:

- Mason Sand is a mixture of crushed limestone aggregate and recycled material that has been washed and properly graded.
- Meets the specifications of ASTM C-144 and ASTM C-897.
- Top size of 2.34mm.

APPLICATION GUIDELINES:

- For use in mortar, grout and plaster mixes. May also be used as a paver base, ground cover or ground stabilizer.

PACKAGING:

- 1 polypropylene bulk bag contains 1 cubic yard of mason sand
- Weight: 2600 lbs
- Dimensions: 48" W x 45" H x 48" L (including pallet and bag)

Limitations: Masonry Sand is a stand-alone product and information provided in this data sheet is representative of Masonry Sand only and not representative of mixtures containing Masonry Sand.



This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about the guidelines for the proper use and application of the covered product(s) under normal environmental and working conditions. Because each project is different, Tileco, Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

For more information on handling this product, please refer to its Safety Data Sheet (SDS).