

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636  
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

# 333-L OMEGASEAL WATER REPELLENT

## 1. PRODUCT DATA

**Date of Preparation:** March 1, 2015  
**Product Name:** 333-L Omegaseal Water Repellent  
**Producer:** Diedrich Technologies, A Hohmann & Barnard Company, 310 Wayto Road, Schenectady, NY 12303  
**Company Contact:** Mike Eglin  
**Telephone:** 800-283-3888  
**24-Hour Emergency Contact:** CHEMTREC 800-424-9300  
*This product is manufactured for Commercial/Industrial use. Not recommended for: Household use.*

## 2. HAZARDS IDENTIFICATION

### GHS Ratings:

**Oral Toxicity:** Acute 3  
**Dermal Toxicity:** Acute 3  
**Skin Irritation:** 2  
**Eye Irritation:** 2  
**Inhalation Toxicity:** Acute 4

### GHS Hazards:

**H301** Toxic if swallowed  
**H311** Toxic in contact with skin  
**H315** Causes skin irritation  
**H319** Causes serious eye irritation  
**H332** Harmful if inhaled

### GHS Precautions

**P261** Avoid breathing dust/fume/gas/mist/vapors/spray  
**P264** Wash hands thoroughly after handling  
**P270** Do not eat, drink or smoke when using this product  
**P271** Use only outdoors or in a well-ventilated area  
**P280** Wear protective gloves/protective clothing/eye protection/face protection  
**P312** Call a POISON CENTER or doctor/physician if you feel unwell  
**P321** Specific treatment (see section 4)  
**P322** Specific measures (see section 4)  
**P330** Rinse mouth  
**P361** Remove/Take off immediately all contaminated clothing  
**P362** Take off contaminated clothing and wash before reuse

**P363** Wash contaminated clothing before reuse  
**P301+P310**  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
**P302+P352**  
IF ON SKIN: Gently wash with plenty of soap and water  
**P304+P340**  
IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing  
**P332+P313**  
IF SKIN irritation occurs: Get medical advice/attention  
**P337+P313**  
IF eye irritation persists: Get medical advice/attention  
**P305+P351+P338**  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
**P405** Store locked up  
**P501** Dispose of contents/container according to local regulations

### Danger



## 3. COMPOSITION

Chemical Name/ CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Aliphatic Solvent 64742-88-7	No Data Found	No Data Found	NIOSH: 350 mg/m <sup>3</sup> TWA 1,800 mg/m <sup>3</sup> Ceiling (15 minutes)

Specific chemical identity and percentage content of ingredients withheld as trade secret pursuant to Massachusetts regulations. Reporting requirements of section 313 title III of the superfund amendments and reauthorization act of 1986 and 10 CFR part 373 apply.

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636  
 EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

#### 4. FIRST AID MEASURES

**Inhalation:** Remove to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention immediately.

**Eye Contact:** Flush with large amounts of water, lift both upper and lower eyelids frequently to assure thorough flushing under lids. Seek medical attention. If irritation persists see a physician.

**Skin Contact:** Wash with mild soap and water and apply skin cream. Remove contaminated clothing and launder before reuse. Discard contaminated shoes. If irritation persists see a physician.

**Ingestion:** If swallowed, do not induce vomiting, contact poison control center. If vomiting occurs keep head below hips to prevent aspiration of liquid into lungs, which can cause chemical pneumonitis, which can be fatal. See a physician immediately.

**Notes to Physician:** No data found.

#### 5. FIRE FIGHTING MEASURES

**Flammable Limits:** LEL= 0.7 UEL= 6.0

**Flash Point:** 105°F

**Extinguishing Media:** Use foam, dry chemical or carbon dioxide.

**Unusual Fire and Explosion Hazards:** Because vapors are heavier than air they may travel along the ground or by ventilation systems far away from material handling point.

**Hazardous Combustion Products:** See Section 10 for a list of hazardous decomposition products for this mixture.

**Fire Fighting:** If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

**Fire Fighting:** Use air supplied breathing apparatus. Use the procedure for fighting petroleum solvent fire.

#### 6. ACCIDENTAL RELEASE MEASURES

Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. Stop leak if you can do it without risk, stay upwind, and avoid run off to waterways and sewers.

**SMALL SPILLS:** Dike and contain. Soak up residue with absorbent, noncombustible material. Scoop into drums appropriate for disposal.

**LARGE SPILLS:** Avoid exposure to sparks, fire or hot metal surfaces. Eliminate possible sources of ignition. If applicable, wear appropriate respirator and other protective residue with absorbent, noncombustible material. Scoop into drum appropriate for disposal. Prevent material from entering drains, sewers or waterways.

#### 7. HANDLING AND STORAGE

**Handling Precautions:** Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated contact with skin. Do not cut, puncture or weld on or near this container. Do not re-use container for any purpose until it has been commercially cleaned. Keep Container closed when not in use. **After containers have been emptied they may contain explosive and/or harmful vapors and residue.**

**Storage:** Keep away from heat, sparks, and open flames. Store away from oxidizing materials. **After containers have been emptied they may contain explosive and/or harmful vapors and residue.**

**Regulatory Requirements:** This product is classified as "Oil" under the Clean Water Act. As such it must be kept out of surface water, watercourses or sewers entering or leading to surface waters.

#### 8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name/ CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Aliphatic Solvent 64742-88-7	No Data Found	No Data Found	NIOSH: 350 mg/m3 TWA 1,800 mg/m3 Ceiling (15 minutes)

**Engineering controls:** Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Ensure that eyewash stations and safety showers are close to the workstation location.

**Ventilation Control:** Local exhaust sufficient to minimize exposure to mist and fumes below permissible exposure limit. If mechanical assist is required, unit must be of an explosion proof type.

**Administrative controls:** No data found.

**Personal Protection:** As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1910.132), employers must perform a hazard Assessment of all workplaces to determine the need for proper protective equipment for each employee.

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636  
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

**Protective Clothing:** Protect all body parts from contact by using full chemical/solvent resistant suit with tight fitting cuffs and collar, rubber boots and full-face shield. Solvent resistant gloves such as nitrile rubber must be worn.

**Eye Protection:** Close fitting safety chemical goggles and face-shield must be worn.

**Skin Protection:** In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact. Apply Diedrich recommended skin barrier cream for additional protection.

**Respiratory:** A NIOSH/MSHA approved air supplied or self-contained respirator must be used if the TLV of the product or component is exceeded. Under specific conditions other NIOSH/MSHA respirators may be permitted under OSHA regulations. Consult with your safety equipment supplier.

**Contaminated Equipment:** Dispose of the waste in compliance with federal, state, regional, and local regulations.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Melting point:** No Data Found

**Freezing point:** No Data Found

**Solubility:** Negligible

**Boiling range:** 315-380°F (157-193°C)

**Flash point:** 105°F

**Evaporation rate:** 0.06

**Flammability:** LEL= 0.7 UEL= 6.0

**Appearance:** Colorless liquid

**Odor:** Light kerosene odor

**Physical State:** Liquid

**Vapor Pressure:** No Data Found

**Odor threshold:** No Data Found

**Vapor Density:** Lower than Air

**Specific Gravity:** 0.86

**pH:** No Data Found

**Explosive Limits:** LEL= 0.7 UEL= 6.0

**% Volatile (by weight):** 80%

**Volatile Organic Components:** 710 g/l

**Partition coefficient (n-Octanol/water):** No Data Found

**Autoignition temperature:** No Data Found

**Decomposition Temperature:** No Data Found

**Viscosity:** No Data Found

**Density:** No Data Found

## 10. STABILITY AND REACTIVITY

**Stability:** STABLE

**Incompatibilities:** No Data Found

**Conditions To Avoid:** Heat, sparks, open flame and fire. Keep away from pilot lights, extinguish all pilot lights in room and adjacent rooms. Be sure to search for multiple pilot lights on appliances.

**Hazardous Decomposition Products:** Carbon monoxide and unidentified organics may be formed during combustion.

## 11. TOXICOLOGICAL INFORMATION

**Routes of Entry:** Inhalation, skin, eyes, ingestion

**Target Organs:** Skin, Eyes, Stomach

**Effects of Overexposure:** Can lead to central nervous system depression producing effects such as headache, dizziness, nausea and loss of consciousness, and even asphyxiation.

CAS Number	Description	% Weight	Carcinogen Rating
None			Not Listed

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** No data found.

## 13. DISPOSAL

Disposal must be at an approved facility for compliance under RCRA Regulations for hazardous waste. Containers must have the proper labeling and be leak proof..

## 14. TRANSPORTATION INFORMATION

The following is for US DOT Highway transportation. Other modes/jurisdictions may have different classifications.

Agency	Proper Shipping Name	UN Number	Packaging Group	Hazard Class
US DOT	Petroleum Distillate, N.O.S.	UN 1268	III	3

## 15 - REGULATORY INFORMATION

No Data Found


310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636  
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

**16. OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

Health	1
Flammability	3
Physical Hazard	0
Personal Protection	<input type="checkbox"/>

**National Fire Protection Association (NFPA)**



**HMIS & NFPA Hazard Rating Legend**

- \* = CHRONIC HEALTH HAZARD
- 0 = INSIGNIFICANT
- 1 = SLIGHT
- 2 = MODERATE
- 3 = HIGH

**LEGEND**

0 = LEAST    1 = SLIGHT    2 = MODERATE    3 = HIGH    4 = EXTREME

N.D. = NOT DETERMINED    N.A. = NOT AVAILABLE    N/A = NOT APPLICABLE

**DISCLAIMER:** While this company believes that the data contained herein are factual and the opinions expressed are based on tests and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by this company as to the effects of such use, the results to be obtained, or the safety and toxicity of the product, nor does this company assume any liability arising out of use, by others, of the product referred to herein. Nor is this information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or governmental regulations.

**REQUIRED SUPPLEMENTAL CONTRACT TERMS:** Failure to obtain a property owner's written acceptance of the enclosed Required Supplemental Terms and Conditions for Restoration Contract shall release any and all of the manufacturer's express or implied warranties (including, without limitation, merchantability and fitness for particular purpose) and user shall indemnify and hold manufacturer harmless from all liability cost and expenses arising in any way from use of or contact with this product. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration Rules of the American Arbitration Association.

Copyright © 2015

Diedrich Technologies is a division of



**Hohmann & Barnard, Inc.**  
30 Rasons Court | Hauppauge, NY 11788  
TEL: 800-645-0616 | FAX: 631-234-0683  
EMAIL: weanchor@h-b.com | www.h-b.com